





NOTES, FEATURES, MATERIALS/FINISHES

NOTES:

- ALL DIMENSIONS IN PARENTHESIS ARE METRIC (mm)
- SPECIALS AVAILABLE UPON REQUEST (MATERIALS, SIZE, MOUNTING HOLES, FINISH, ETC...)
- ADD 'M' TO END OF PART NUMBER FOR METRIC INSERTS


FEATURES:

- RUGGED ALL METAL CONSTRUCTION
- UNEQUALLED TEMP. RANGE: -200°F TO 500°F
- THREE AXIS CAPABILITY (6 DOF)
- HIGH DAMPING: C/Cc ≈ .15-.20
- LONG LIFE AND MAINTENANCE FREE

MATERIALS/FINISHES:

- CABLE: 300 SERIES SS PER MIL-W-83420 OR RR-W-410
- INSERTS: 300 SERIES SS PER MS124655
- RETAINER BARS: 6063-T52 ALUMINUM ALLOY/CHEM FILM IAW MIL-C-5541, CLASS 1A

PART NUMBER	DIMENSIONS in (mm)			ISOLATOR WEIGHT oz (gms)	COMPRESSION		ROLL		COMPRESSION/ROLL	
	H ±.03	Wf (REF)	Wd (REF)		Kv (VIBE) (lbs/in)	Ks (SHOCK) (lbs/in)	Kv (VIBE) (lbs/in)	Ks (SHOCK) (lbs/in)	Kv (VIBE) (lbs/in)	Ks (SHOCK) (lbs/in)
SM5-100-A	1.00 (25,4)	1.71 (43,4)	2.24 (56,9)	0.80 (22,7)	94	74	54	57	64	50
SM5-120-A	1.20 (30,5)	1.90 (48,3)	2.50 (63,5)	1.00 (28,4)	60	46	31	34	45	31
SM5-145-A	1.45 (36,8)	2.10 (53,3)	2.73 (69,3)	1.10 (31,2)	40	23	20	20	28	18



5/32" DIAMETER CABLE

Square Mount Isolator

